

**We Claim:**

1. An enclosure for a worktable having a top and four corner support posts with an undershelf releasably secured to the posts below the worktable top, the enclosure comprising:

a pair of opposed side panels each including front and back vertical curved portions for placement around opposed pairs of front and back support posts;

a lintel releasably attached to a front underside of the worktable and the front vertical curved positions of the opposed side panels; and

a pair of front doors secured in place below the lintel and above the undershelf constructed and arranged to provide access to a space between the worktable and undershelf.

2. An enclosure as in claim 1 further including contoured post covers, one for each support post, positioned around interior portions of the posts and secured to the vertical curved portions of the side panels.

3. An enclosure as in claim 1 wherein each of the opposed side panels includes a lower inwardly disposed horizontal flange at a lower portion thereof secured to the undershelf.

4. An enclosure as in claim 1 wherein each of the opposed side panels includes an upper inwardly disposed horizontal flange at an upper portion thereof abutting the worktable top.

5. An enclosure as in claim 1 wherein the front doors are hingedly secured to the front vertical curved portion of the opposed side panels.

6. An enclosure as in claim 5 wherein the lintel includes a recessed door stop portion with magnets for releasably holding the front doors against the stop in a closed position.

7. An enclosure as in claim 1 wherein the lintel includes downwardly facing dual parallel tracks and the undershelf includes upwardly facing dual parallel tracks, and wherein the front doors are slideably mounted in the tracks for side-to-side movement.